


Illumipod LQgic™ 6 Optic 25 RGB  
Item Number: 21006001

ILUMINARC®

## SPECIFICATION



- Compatible with LQgic™ system devices
- Light weight and durable construction
- Plenum rated cable
- High power 1 W (350 mA) LEDs
- Direct replacement for MR16



### Physical

Length: 3.8 in (96 mm)  
Diameter: 1.96 in (50 mm)  
Height: 3.8 in (96 mm)  
Weight: .4 lbs (.2 kg)

### Optics

Light source: 6 x 1 W 350 mA (2 Red, 2 Green, 2 Blue) LEDs  
Minimum LED lifetime: 50,000 hrs based on manufacturers specifications

*JOB INFORMATION* Type: \_\_\_\_\_

Job Name: \_\_\_\_\_

Cat. Number: \_\_\_\_\_


Notes:

5200 NW 108<sup>th</sup> Ave. Sunrise FL, 33351  
WWW.ILUMINARC.COM (954) 923-3680

# Illumipod LQgic™ 6 Optic 25 RGB

Item Number: 21006001

ILUMINARC®

<b>Construction</b>	Color: Silver Housing: Cast aluminum Protection rating: IP20
<b>Control</b>	Determined by software installed into LQgic™ driver that has been selected
<b>Installation</b>	Orientation: Any Minimum distance to illuminated surface: 4 in (92 mm)
<b>Connections</b>	Power and data cable entry: Belden 1585A plenum rated with RJ45 connector 79 in (2,000 mm)
<b>Electrical</b>	Power supply: LQgic™ driver
<b>Input current</b>	350 mA @ 48 V
<b>Power consumption</b>	11.3 W
<b>Thermal</b>	Cooling: Convection Maximum ambient temperature (Ta max): 40° C (104° F)
<b>Approvals</b>	 CONFORMS TO UL STD. 1973 CERTIFIED TO CSA STD. C22.2 No. 100
<b>Included items</b>	Illumipod LQgic™ 6 Optic RGB Warranty Card User Manual
<b>Accessories</b>	Trim ring: Brushed aluminum (66666001) Trim ring: White (66666002)

Specification subject to change without notice

*JOB INFORMATION* Type: \_\_\_\_\_

Job Name: \_\_\_\_\_

Cat. Number: \_\_\_\_\_

Notes:


5200 NW 108<sup>th</sup> Ave. Sunrise FL, 33351  
WWW.ILUMINARC.COM (954) 923-3680

# Ilumipod LQgic™ 6 Optic 25 RGB


Item Number: 21006001

ILUMINARC®

Filename: Ilumipod Logic 6 Optic 25 RGB-  
RGB\_IESNA2002  
 Manufacturer: ILUMINARC  
 Luminaire: ILUMIPOD LOGIC 6 OPTIC RGB 25 DEGREE  
 Luminaire Cat: 21006001  
 Lamp: 2 RED,2 GREEN,2 BLUE  
 Lamp Output: 1 lamp(s), rated Lumens/lamp: 230  
 Max Candela: 514.3 at Horizontal: 90, Vertical: 5  
 Input Wattage: 11.3  
 Luminous Opening: Point  
 Test: 2009430RGB  
 Test Lab: Iluminarc R&D Optics Laboratory  
 Photometry : Type B  
 CIE Class: Direct  
 Cutoff Class: Full Cutoff



Flood Summary				
	Efficiency	Lumens	Horizontal Spread	Vertical Spread
Field (10%):	41%	94.2	47.1	47.7
Beam (50%):	20.1%	46.2	23.3	23.1
Total:	52.7%	121.3		



Photometrics Pro 1.3.2 copyright 2003-2008 by jSolutions, Inc.  
 Reported data calculated from manufacturer's data file, based on IES recommended methods.

*JOB INFORMATION* Type: \_\_\_\_\_

Job Name: \_\_\_\_\_

Cat. Number: \_\_\_\_\_

Notes:

5200 NW 108<sup>th</sup> Ave. Sunrise FL, 33351  
 WWW.ILUMINARC.COM (954) 923-3680