

LOGIC™ 16x36
Item Number: 316x36001

ILUMINARC®

SPECIFICATION

PRELIMINARY INFORMATION

- 1, 2, 3, 4, 6, or 8-channel DMX control
- RGB color mixing with or without outboard DMX controller
- Recall custom programs via master/slave or DMX
- Upload software over RS-232 connection
- Schedule playback with time clock functions
- Master/slave over RJ-45 connections

Physical


Length: 21 in (532 mm) does not include mounting solution
Width: 5.7 in (145 mm) does not include mounting solution
Height: 4.6 in (119 mm) does not include mounting solution
Weight: 9.2 lbs (4.2 kg) does not include mounting solution

JOB INFORMATION Type: _____

Job Name: _____

Cat. Number: _____

Notes:

Construction	Color: Beige powder coat Housing: Steel Protection rating: IP20
Control	Operating modes: RGB 1-channel: RGB, dimmer (no individual RGB adjustments) 3-channel: RGB control (individual RGB adjustments) 4-channel: RGB control, dimmer 48-channel: RGB line control 53-channel: RGB line control, dimmer, color macro, strobe, auto + custom, auto speed White 1-channel: White dimmer 2-channel: White control (warm + cool) 2-channel: White macro, dimmer 3-channel: White control (warm + cool), dimmer 5-channel: White control (warm + cool), macro, dimmer, strobe 32-channel: White line control (warm + cool) 37-channel: White line control (warm + cool) dimmer, color macro, strobe, auto + custom, auto speed Stand alone: Color mixing with or without DMX controller Recall custom programs via master/slave or DMX Control protocol: USITT DMX 512
Installation	Orientation: Any
Connections	Power cable entry: IES inlet Power cable: 60in (1524mm) Data cable entry: RJ-45 Data cable: Data in: RJ-45 to 3 pin male, data out: RJ-45 to 3 pin female
Electrical	AC power: 100 ~ 240 V, 50/60 Hz Power supply: Internal, auto-ranging, multi-voltage
Power and current	120 V, 60 Hz: 650 W, 5.4 A operating, . 230 V, 50 Hz: 650 W, 2.8 A operating,
Thermal	Cooling: Convection Maximum ambient temperature (Ta max): 40° C (104° F)
Approvals	 CONFORMS TO UL STD. 1573 CERTIFIED TO CSA STD. C22.2 No. 166 3144482
Included items	1 x LOGIC™ 16x36 1 x RJ-45 to 3 pin DMX male adapter (input) 1 x RJ-45 to 3 pin DMX female adapter (output) 1 x IEC power cable with plug: 60in (1524mm) Warranty Card User QSG

Specifications subject to change without notice

5200 NW 108th Ave. Sunrise FL, 33351
WWW.ILUMINARC.COM (954) 923-3680

JOB INFORMATION Type: _____

Job Name: _____

Cat. Number: _____

Notes: