


Illumipanel 48 IP Optic 15 WW
 Item Number: 13048006

ILUMINARC®

SPECIFICATION



- 2, 3, or 6-channel DMX-512 LED wash light (with ID addressing)
- Variable white color mixing with or without DMX controller (2,800 K ~ 7,000 K)
- Recall custom programs via master/slave or DMX
- IP66
- High Power (600 mA) LEDs



Physical

Length: 15 in (380 mm)
 Width: 7.5 in (190 mm)
 Height: 7.8 in (198 mm)
 Weight: 9.5 lbs (4.3 kg)

Optics

Light source: 48 x 600 mA (34 warm white, 14 cool white) LEDs
 Minimum LED lifetime: 50,000 hrs based on manufacturer's specifications

JOB INFORMATION Type: _____

Job Name: _____

Cat. Number: _____

Notes:

Ilumipanel 48 IP Optic 15 VW

Item Number: 13048006

ILUMINARC®

Construction	Color: UV resistant gray powder coat, custom colors available Housing: Cast aluminum Lens cover: Tempered glass Protection rating: IP66
Control	Operating modes: 2 channel: cool white, warm white control 3 channel: cool white, warm white, dimmer 2 channel: master dimmer, color temp macros 6 channel: master dimmer, cool white, warm white, color temp macros, strobe, and ID addressing Stand alone: Color temperature mixing with or without DMX controller Recall custom programs via master/slave or DMX Control protocol: USITT DMX 512
Installation	Orientation: Any Minimum distance to illuminated surface: 4 in (92 mm)
Connections	Power cable entry: IP66 stainless steel cable gland Power cable: Power in: 21.5 in (546 mm), power out: 20 in (508 mm) Data cable entry: IP66 stainless steel cable gland Data cable: Data in: 22 in (559 mm), data out: 18 in (470 mm)
Electrical	AC power: 100 ~ 240 V, 50/60 Hz Power supply: Internal, auto-ranging, multi-voltage
Power and Current	120 V, 60 Hz: 103.8 W, .9 A operating, 1 A inrush 230 V, 50 Hz: 100 W, .4 A operating, .6 A inrush
Power Linking	120 V: 10 units max 230 V: 20 units max
Thermal	Cooling: Convection Maximum ambient temperature (Ta max): 40° C (104° F)
Approvals	 <p>CONFORMS TO UL STD. 1973 CERTIFIED TO CSA STD. C22.2 No. 186 3144482</p>
Included items	ILUMIPANEL 48 IP VW Power cable with plug: 65 in (1,651 mm) IP66 power extension cable: 103 in (2,604 mm) IP66 signal extension cable: 103 in (2,604 mm) DMX input cable: 6.5 in (165 mm) DMX output cable: 6.5 in (165 mm) 7.5 in gel frame (max thickness 4 mm) Warranty Card User Manual
Accessories	16.4 ft (5 m) power extension cable 16.4 ft (5 m) signal extension cable

Specification subject to change without notice

JOB INFORMATION Type: _____

Job Name: _____

Cat. Number: _____


Notes:

Illumipanel 48 IP Optic 15 VW


Item Number: 13048006

ILUMINARC®

Filename: Illumipanel 48 IP Optic 15 VW 100% ALL
 Manufacturer: ILUMINARC
 Luminaire: Illumipanel 48 IP Optic 15 VW
 Lamp: 34 Warm White, 14 Cool White
 Lamp Output: 1 lamp(s), rated Lumens/lamp: 3500
 Max Candela: 17,522.9 at Horizontal: 0, Vertical: 0
 Input Wattage: 111.3
 Luminous Opening: Point
 Test: 2009 ALL
 Test Lab: Illuminarc R & D Optics Laboratory
 Photometry : Type B
 CIE Class: Direct
 Cutoff Class: Full Cutoff
Filename: Illumipanel 48 IP Optic 15 VW 100% ALL



Flood Summary				
	Efficiency	Lumens	Horizontal Spread	Vertical Spread
Field (10%):	48.3%	1,690.1	34.4	34.5
Beam (50%):	24.2%	847.3	17.3	17.1
Total:	62.5%	2,186.0		



Photometrics Pro 1.3.2 copyright 2003-2008 by jSolutions, Inc.
 Reported data calculated from manufacturer's data file, based on IES recommended methods.

JOB INFORMATION Type: _____

Job Name: _____

Cat. Number: _____

Notes: