


Illumipod LQgic™ 6 Optic 25 VW  
Item Number: 21006002

ILUMINARC®

## SPECIFICATION



- Compatible with LQgic™ system devices
- Light weight and durable construction
- Plenum rated cable
- High power 1 W (350 mA) LEDs
- Direct replacement for MR16



### Physical

Length: 3.8 in (96 mm)  
Diameter: 1.96 in (50 mm)  
Height: 3.8 in (96 mm)  
Weight: .4 lbs (.2 kg)

### Optics

Light source: 6 x 1 W 350 mA (2 cool white, 4 warm white) LEDs  
Minimum LED lifetime: 50,000 hrs based on manufacturers specifications

*JOB INFORMATION* Type: \_\_\_\_\_


Job Name: \_\_\_\_\_

Cat. Number: \_\_\_\_\_

Notes:

Illumipod LQgic™ 6 Optic 25 VW  
Item Number: 21006002

ILUMINARC®

<b>Construction</b>	Color: Silver Housing: Cast aluminum Protection rating: IP20
<b>Control</b>	Determined by software installed into LQgic™ driver that has been selected
<b>Installation</b>	Orientation: Any Minimum distance to illuminated surface: 4 in (92 mm)
<b>Connections</b>	Power and data cable entry: Belden 1585A plenum rated with RJ45 connector 79 in (2,000 mm)
<b>Electrical</b>	Power supply: LQgic™ driver
<b>Input current</b>	350 mA @ 48 V
<b>Power consumption</b>	11.3 W
<b>Thermal</b>	Cooling: Convection Maximum ambient temperature (Ta max): 40° C (104° F)
<b>Approvals</b>	 CONFORMS TO UL STD. 1573 CERTIFIED TO CSA STD. C22.2 No. 195 3144482
<b>Included items</b>	Illumipod LQgic™ 6 Optic VW Warranty Card User Manual
<b>Accessories</b>	Trim ring: Brushed aluminum (66666001) Trim ring: White (66666002)

Specification subject to change without notice

*JOB INFORMATION* Type: \_\_\_\_\_

Job Name: \_\_\_\_\_

Cat. Number: \_\_\_\_\_


Notes:

# Ilumipod LQgic™ 6 Optic 25 VW


Item Number: 21006002

ILUMINARC®

Filename: Ilumipod Logic 6 Optic 25 VW 100% ALL  
 Manufacturer: ILUMINARC  
 Luminaire: Ilumipod Logic 6 Optic 35 VW  
 Lamp: 4 Warm White, 2 Cool White  
 Lamp Output: 1 lamp(s), rated Lumens/lamp: 320  
 Max Candela: 448.0 at Horizontal: 180, Vertical: 5  
 Input Wattage: 11.9  
 Luminous Opening: Point  
 Test: 2009 ALL  
 Test Lab: Iluminarc R & D Optics Laboratory  
 Photometry : Type B  
 CIE Class: Direct  
 Cutoff Class: Full Cutoff  
 Filename: Ilumipod Logic 6 Optic 25 VW 100% ALL



Flood Summary				
	Efficiency	Lumens	Horizontal Spread	Vertical Spread
Field (10%):	48.1%	154.0	66.2	67.1
Beam (50%):	23%	73.6	30.9	30.3
Total:	61.3%	196.1		



Photometrics Pro 1.3.2 copyright 2003-2008 by jSolutions, Inc.  
 Reported data calculated from manufacturer's data file, based on IES recommended methods.

*JOB INFORMATION* Type: \_\_\_\_\_

Job Name: \_\_\_\_\_

Cat. Number: \_\_\_\_\_

Notes: